



**DACHHAKEN UK BIBER/SCHIEFER HL (OHNE HOLZSCHRAUBE)**  
**ROOF HOOK UK PLAIN TILES/SLATES HL (WITHOUT WOOD SCREW)**

**420184**

170x240x35 mm

0,74 kg

Set ist vormontiert

**Abmessung Grundplatte:** 55 x 35 mm

**Material:** Edelstahl; Verzinkter Stahl

**Materialstärke:** 8,0 mm

**Schraube Ø:** M8

**Geeignet für:** Holz

**Dacheindeckung:** Ziegeldach

**# Schrauben pro Stück:** 2 x 6,0

**Höhenverstellung:** 20,00 mm

**Schutzdauer Verzinkung nach**  
**EN ISO 14713-1:2017**

**Verzinkung Schutzdauer in**  
**Korrosionskategorie C3 (mittlere Verun-**  
**reinigung oder leichte Chloridbelastung):**  
26-78 Jahre

**Verzinkung Schutzdauer in**  
**Korrosionskategorie C4 (hohe Ver-**  
**unreinigung oder beträchtliche**  
**Chloridbelastung):** 13-26 Jahre

**Für Einsatz in**  
**Korrosionskategorie C5 ( sehr hohe Verun-**  
**reinigung und wesentliche Chloridbelas-**  
**tung z.B. Küstenbereiche) nicht geeignet**

170x240x35 mm

0,74 kg

Set pre-assembled

**Dimensions base plate:** 55 x 35 mm

**Material:** Stainless steel; Galvanised steel

**Material thickness:** 8,0 mm

**Screw Ø:** M8

**Applicable with:** Wood

**Roof decking:** Tiled roof

**# of screws:** 2 x 6,0

**Height adjustment:** 20,00 mm

**Duration of protection Zinc coating**  
**according to EN ISO 14713-1:2017**  
**Zinc coating Duration of protection in**  
**Corrosion category C3 (medium con-**  
**tamination or light chloride load):**  
26-78 years

**Verzinkung Schutzdauer in**  
**Korrosionskategorie C4 (hohe Verunrei-**  
**nigung oder beträchtliche Chloridbelastung):**  
13-26 years

**For use in Corrosion category C5**  
**(very high contamination andes-**  
**sential chloride contamination**  
**e.g. coastal areas) not suitable**