

## **SUNSYNK-W5.3**



## **DATASHEET**

www.sunsynk.com sales@sunsynk.com customerservices@sunsynk.com



Model		SUNSYNK-W5.3
Main Parameter		
Battery Chemistry		LiFePO <sub>4</sub>
Capacity (Ah)		104
Scalability		Max.32 pcs in parallel (170kWh)
Nominal Voltage (V)		51.2
Operating Voltage (V)		43.2~57.6
Energy (kWh)		5.32
Usable Energy (kWh) [1]		4.79
Charge/Discharge Current (A)	Recommend [2]	50
	Max. <sup>[2]</sup>	100
	Peak (2mins,25°C)	150
Other Parameter		
Recommend Depth of Discharge		90%
Dimension (W x H x D)		$440 \times 620 \times 135$ (doesn't include terminals,
Difficusion (W X 11 X		circuit breaker, hanging boards, and pedestal)
Weight (kg)		46
Master LED Indicator		5 LED (SOC 20%~100%)
		3 LED (working, alarming, protecting)
IP Rating of Enclosure		IP65
Working Temperature		Charge: -10°C ~ +55°C
		Discharge: -20°C ~ +55°C
Storage Temperature		0°C ~ +35°C
Humidity		5% ~ 95%
Altitude		≤2000m
Cycle Life		≥6000 (25±2°C,90%DOD,0.5C/1C,70%EOL)
Installation		Wall-Mounted (supports 19-inch standard cabinet)
Communication Port		CAN2.0, RS485
Life Cycle Power During Warranty Period [3]		16MWh@70%EOL
Certification		IEC62619, CE, UK, CEC, UN38.3

 $<sup>^{[1]}</sup>$  DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25° C. System usable energy may vary due to system configuration parameters.

<sup>[3]</sup> The warranty is due whichever reached first of warranty period or energy throughout.





<sup>[2]</sup> The current is affected by temperature and SOC.





- 📞 Call us: +44 151 832 4300 Email us: sales@sunsynk.com
- HK Address: Room 702-704, 7/F Texwood Plaza, 6 How Ming Street, Kwun Tong, Kowloon, Hong Kong.
- UK Address: Sunsynk UK Ltd, 17 Turnstone Business Park, Mulberry Avenue, Widnes, Cheshire, WA8 0WN.
- SA Address: Globaltech Sunsynk South Africa (Pty) Ltd, Unit 2 Highview Boulevard, Ferndale 2194.
- NL Address: Sunsynk NL BV, Henri Wijnmalenweg 8, 5657 EP Eindhoven, Netherlands.











