



mounting systems



## 2-Post Steel ProLine

<b>Application</b>	Ground mount
<b>PV-Modules</b>	Framed
<b>Module arrangement</b>	Up to 55 m per rack unit
<b>Module orientation</b>	Portrait, 2 modules on top of each other Landscape, 4 modules on top of each other
<b>Max. Module sizes</b>	Upright: 2300 mm x unlimited Landscape: 2300 x 1013 mm
<b>System inclination</b>	20° or 25°
<b>Minimum module elevation to the ground</b>	70 - 80 cm
<b>Max. ground inclination</b>	Up to 10° in east-west direction
<b>Foundation options</b>	Cap profile (rammed post), foot plates with fix anchors
<b>Frame profiles</b>	Steel (S 355/S 350 GD)
<b>Small parts</b>	Steel galvanized, stainless steel, geomet-coated steel, extruded aluminum (EN AW 6063 T66)
<b>Warranty</b>	10 years



Open Terrain




Framed Module




Orientation Portrait



Orientation Landscape



Connection detail support - rafter



Connection detail post



Connection detail module support

Configuration	Module	Foundation	Clamping
2-Post Steel 2 portrait	Framed modules	Cap profile, Foot plates	Clickstones
2-Post Steel 4 landscape			Clickstones

